

PRODUCT SPECS

HOSE REEL

Model HRV 4000, HRV 5000 + HRV 6000



HRV 5000
shown

SPECIFICATIONS

Controls	Variable speed 10-15 RPM Forward/Reverse Foot switch activation
Power requirements.....	120V/15A
Motor	1 HP DC motor
Drive system	Belt drive
Load	Forklift + sling
Hose loops	5/8" x 500' w/ 3/4" quick connects pre-charged with glycol
Hose capacity....	HRV 4000: 8 x 500' loops = 4,000' HRV 5000: 10 x 500' loops = 5,000' HRV 6000: 12 x 500' loops = 6,000'
Weight.....	HRV 4000: 2,025 lbs HRV 5000: 2,520 lbs HRV 6000: 3,015 lbs
Dimensions	HRV 4000: 48" l x 43" w x 56" h HRV 5000: 46" l x 52" w x 62" h HRV 6000: 52" l x 48" w x 69" h

FEATURES

- The reel's primary purpose is to store and reel ground thaw hose on job sites.
- The modular design offers more flexibility over built-in reels, including the option of storing the hose reel at a secure location on or off the job site when not in use. This makes it easier to deploy or collect hose on more more than one job site.
- Variable speed drive provides the operator full control of the reel speed, for safe and comfortable winding or unwinding of the hose.
- Releasing belt tension allows the hose to freewheel out for deployment of the hose by a single operator. The slip clutch on the belt drive provides additional safety.
- Fork pockets for ease of placement.
- Oversized foot pedal accommodates steel toe boots.
- Electronics are sealed to NEMA 4X weatherproofing standards.
- Large footprint skid provides superior weight distribution.

COVERAGE

HRV 4000: THAW 6,000 ft sq
CURE 8,000 ft sq

HRV 5000: THAW 7,500 ft sq
CURE 10,000 ft sq

HRV 6000: THAW 9,000 ft sq
CURE 12,000 ft sq



400 Service Road, St. Brieux, SK, S0K 3V0, Canada
1-888-750-1700 | WWW.DRYAIR.CA